



Chain link fences – IDEAL®

- high quality fences made of steel wires with galvanized or galvanized + PVC finish
- round galvanized or galvanized + PVC posts with cap and tension wire clamp are recommended to be used for the assembly
- it is also recommended to use tension wires, binding wires, stretchers and posts with the same galvanized or galvanized + PVC finish

IDEAL® galvanized + PVC 50

description	color	height (mm)	roll length (m)
eyelets 55 × 55 mm	green	1000	15
wire diameter 2,50 mm	green	1000	25
15, 25 m long compact roll	brown	1000	25
RAL 6005 – green,	anthracite	1000	25
RAL 8014 – brown	green	1250	15
RAL 7016 – anthracite	green	1250	25
	brown	1250	25
	anthracite	1250	25
	green	1500	15
	green	1500	25
	brown	1500	25
	anthracite	1500	25
	green	1600	15
	green	1600	25
	brown	1600	25
	anthracite	1600	25
	green	1800	15
	green	1800	25
	brown	1800	25
	anthracite	1800	25
	green	2000	15
	green	2000	25
	brown	2000	25
	anthracite	2000	25



(tension wire not included;
must be ordered separately)

Note: colour white, blue, grey
– price on request.



IDEAL® galvanized + PVC – round non-interlaced roll

description	color	height (mm)	roll length (m)
eyelets 55 × 55 mm	green	1000	15
wire diameter 2,50 mm	green	1000	25
RAL 6005 – green 15, 25 m long	anthracite	1000	25
RAL 7016 – anthracite 25 m long (including tension wire)	green	1250	15
	green	1250	25
	anthracite	1250	25
	green	1500*	15
	green	1500*	25
	anthracite	1500*	25
	green	1600*	15
	green	1600*	25
	anthracite	1600*	25
	green	1800*	15
	green	1800*	25
	anthracite	1800*	25
	green	2000*	15
	green	2000*	25
	anthracite	2000*	25



* from a height of 1500 mm,
it is recommended to add
a center tensioning wire
(not included in the package)



IDEAL® galvanized + PVC 50 – SUPER

description	height (mm)
eyelets 55 × 55 mm	1000
wire diameter 3,00 mm	1250
25 m long compact roll	1500
RAL 6005 – green	1600
(tension wire not included; must be ordered separately)	1800
	2000



IDEAL® galvanized

description	height (mm)
eyelets 55 × 55 mm	1000
wire diameter 2,00 mm	1250
25 m long compact roll	1500
(tension wire not included; must be ordered separately)	1600
	1800
	2000



IDEAL® galvanized – round interlaced roll

description	height (mm)	roll length (m)
eyelets 55 × 55 mm	1000	15
wire diameter 2,00 mm	1000	25
15 and 25 m long roll (including tension wire)	1250	15
	1250	25
	1500*	15
	1500*	25
	1600*	15
	1600*	25
	1800*	15
	1800*	25
	2000*	15
	2000*	25

* from a height of 1500 mm,
it is recommended to add
a center tensioning wire
(not included in the package)

USE: gardens, factories and warehouses...

IDEAL[®] galvanized + PVC 45 – TENNIS

- offer for fencing of court to height 3,0; 3,5; 4,0 m
- fencing mesh in rolls according to standard dimensions of court (18 × 36 m), i.e. roll at 18 meters

description	height (mm)	roll length (m)
eyelets 45 × 45 mm wire diameter 1,80/2,70 mm RAL 6005 – green	3000	18
	3500	18
	4000	18



Posts and post supports IDEAL[®] galvanized + PVC – TENNIS

description	height (mm)	diameter (mm)
round posts IDEAL [®] RAL 6005 – green post includes the plastic cap (no clamp for tensioning wire)	3750	60
	4300	60
	4900	60
	5200	60




post supports IDEAL [®] RAL 6005 – green including plastic cap and fasteners	3500	48
	4000	48
	4750	48



Wicket IDEAL[®] galvanized + PVC – TENNIS

description	height (mm)	width (mm)
wicket IDEAL [®] TENNIS for tennis courts RAL 6005 – green frame made of round sections (closed) square mesh paneling eyelets 45 × 45 mm wire diameter 2,70 mm wicket consists of 2 posts, including pivot hinges included is the lock with FAB lock insert	2200	1250



Tension wire IDEAL[®] galvanized + PVC

description	color	length (m)
roll 26, 52 and 78 m wire diameter 3,40 mm RAL 6005 – green	green	26 (green label)
RAL 8014 – brown	green	52 (white label)
RAL 7016 – anthracite	green	78 (green label)
	brown	52 (white label)
	brown	78 (green label)
	anthracite	52 (white label)
	anthracite	78 (green label)



Tension wire galvanized

description	length (m)
roll 52 and 78 m wire diameter 3,00 mm	52 (white label)
	78 (green label)



RECOMMENDATION:

- no center tension wire technologically possible to interlock during production and must be stretched independently
- center tension wire is included with meshes with height beginning at 1,5 m



Accessories for the installation of chain link fences

description	
	tensioner with galvanized finish
    	tensioner with galvanized + PVC finish RAL 6005 – green RAL 8014 – brown RAL 9010 – white RAL 5010 – blue RAL 7016 – anthracite
	green
	brown
	white
	blue
	anthracite
	tensioner SUPER with galvanized + PVC finish – green
	KOMBI galvanized tensioner
	KOMBI galvanized + PVC tensioner
	tension comb IDEAL® for stretching square meshes having heights up to 1500 mm (in primer coat)
	tension comb IDEAL® for stretching square meshes having heights above 1500 mm (in primer coat)
	pliers IDEAL® PROFI
	brace IDEAL® galvanized
	brace IDEAL® galvanized
	brace IDEAL® galvanized + PVC RAL 6005 – green
	brace IDEAL® galvanized + PVC RAL 6005 – green
	brace IDEAL® galvanized + PVC RAL 7016 – anthracite
	brace IDEAL® galvanized + PVC RAL 7016 – anthracite

Binding wires

description	wire thickness (mm)	length (m)
	1,0	100
	1,2	100
	1,0	24
	1,4	50
	1,8	50
	1,4	60
	–	100
	1,4	24
   	1,4	50
	1,4	50
	1,4	50
	1,4	50
	2,6	25
	0,65	–
	0,65	–