




Posts and post supports

FIVE-STAGE PROTECTION OF FRAME AND POSTS:

- 1 degreasing
- 2 phosphating
- 3 demineralized water rinse 3x
- 4 passivation (Envirox "SG" process)
- 5 polymer paint layer 80 µm



Round posts – IDEAL®


- strongly galvanized
- the technologies we use ensure at least **double the corrosion resistance** on iron and galvanized materials (salt fog testing in a chamber)
- this is the **highest level of surface treatment** and painting in the Czech Republic

description	height/diameter/wall thickness (mm)
 POST	1750/38/1,25
galvanized	2000/38/1,25
black plastic cap	2300/38/1,25
black tension wire clamp	2600/38/1,50
included with post	1500*/48/1,50
* tension wire clamp is not included with post	1750*/48/1,50
	2000*/48/1,50
	2100/48/1,50
	2400/48/1,50
	2600/48/1,50
	3000/48/1,50
 POST	1750/38/1,25
galvanized + PVC	2000/38/1,25
green plastic cap	2300/38/1,25
green tension wire clamp	2600/38/1,50
included with post	1500*/48/1,50
RAL 6005 – green	1750*/48/1,50
* tension wire clamp is not included with post	2000*/48/1,50
	2100/48/1,50
	2400/48/1,50
	2600/48/1,50
	3100/48/1,50
 POST	1750*/48/1,50
galvanized + PVC	2000*/48/1,50
black plastic cap	2400*/48/1,50
RAL 7016 – anthracite	2600*/48/1,50
* tension wire clamp is not included with post	



Round post supports – IDEAL®

- strongly galvanized
- post supports are cut on the top to be anchored to posts with plastic ends
- bonding material is included
- IDEAL®** post supports are also used for **PILCLIP®** posts



description	height/diameter/wall thickness (mm)
 POST SUPPORT	1750/38/1,25
galvanized	2000/38/1,25
	2500/38/1,25
 POST SUPPORT	1750/38/1,25
galvanized + PVC	2000/38/1,25
RAL 6005 – green	2500/38/1,25
	2700/38/1,50
	3000/38/1,50
	3000/48/1,50
 POST SUPPORT	2000/38/1,25
galvanized + PVC	2500/38/1,25
RAL 7016 – anthracite	








Square posts for PILOFOR® panels

PILOFOR® posts 60 × 60 mm for PILOFOR® panels





FIVE-STAGE PROTECTION OF POSTS:

- 1 degreasing
- 2 phosphating
- 3 demineralized water rinse 3x
- 4 passivation (Envirox "SG" process)
- 5 polymer paint layer 80 µm



description	height of post (mm)	galvanized	galvanized + PVC RAL 6005	galvanized + PVC RAL 7016
 <p>square section 60 × 60 mm wall thickness 1,50 mm posts are provided with pressed M6 nuts and black PVC cap RAL 6005 – green</p> <p>  </p>	1500	✓	✓	–
	1700	✓	✓	✓
	2000	✓	✓	✓
	2200	✓	✓	–
	2400	✓	✓	✓
	2600	✓	✓	✓
	2800	✓	✓	–
	3000	✓	✓	–
	3200	✓	✓	–
	Other colors of posts can be ordered separately.			




PILODEL® posts 60 × 40 mm for PILOFOR® panels




description	height of post (mm)	galvanized	galvanized + PVC RAL 6005	galvanized + PVC RAL 7016
 <p>rectangular section 60 × 40 mm wall thickness 1,50 mm posts are provided with black PVC cap RAL 6005 – green, RAL 7016 – anthracite</p> <p>  </p>	1500	✓	✓	–
	1700	✓	✓	✓
	2000	✓	✓	✓
	2200	✓	✓	✓
	2400	✓	✓	✓
	2600	✓	✓	✓
	3000	✓	✓	–
	3200	✓	✓	–
	Other colors of posts can be ordered separately.			

Posts with fixation strip PILCLIP®

- the technologies we use ensure at least **double the corrosion resistance** on iron and galvanized materials (salt fog testing in a chamber)
- this is the **highest level of surface treatment** and painting in the Czech Republic
- thanks to the pressed "V" shaped beam, the PILCLIP® post has much **greater rigidity and solidity** compared to common round posts (e.g. the PILCLIP® 48 mm in diameter is equivalent to a common round post with a diameter of 60 mm)
- installing fences** on PILCLIP® posts **is more sophisticated and convenient for the user** compared to round posts



description	height/diameter/wall thickness (mm)
 <p>POST galvanized + PVC green PVC cap included with post RAL 6005 – green</p> <p> </p>	1700/48/1,50
	2000/48/1,50
	2300/48/1,50
	2500/48/1,50
	2700/48/1,50
	3000/48/1,50

description	height/diameter/wall thickness (mm)
 <p>POST galvanized + PVC black PVC cap included with post RAL 7016 – anthracite</p> <p> </p>	1700/48/1,50
	2000/48/1,50
	2300/48/1,50
	2500/48/1,50