





Industrial welded panels PILOFOR® ECO, LIGHT

- · rectangular loops
- anchored to round posts with a diameter of 48 mm (ECO, LIGHT)
- · panel width 2500 mm
- modified galvanized and galvanized + PVC RAL 6005 green, RAL 7016 anthracite

PILOFOR® ECO PANELS WITH PROFILE

description	height (mm)	PILOFOR ECO galvanized + PVC RAL 6005	recommended post height	recommended number of anchorings to post	number of incorporated "V" shapes
eyelets 75 × 200 mm	1230	V	1700	4	2
wire diameter 4 mm	1530	✓	2000	4	3
	1730	✓	2400	4	3

PILOFOR® LIGHT PANELS WITH PROFILE

description	height (mm)	PILOFOR LIGHT galvanized	recommended post height	recommended number of anchorings to post	number of incorporated "V" shapes
eyelets 50 × 200 mm	1030	V	1500	3	2
wire diameter 4 mm	1230	V	1700	4	2
	1530	V	2000	4	3
	1730	V	2400	4	3
	2030	✓	2600	4	4

description	height (mm)	PILOFOR LIGHT galvanized + PVC RAL 6005	PILOFOR LIGHT galvanized + PVC RAL 7016	recommended post height	recommended number of anchorings to pos	number of incorporated it "V" shapes
eyelets 50 × 200 mm	1030	V	V	1500	3	2
wire diameter 4 mm	1230	✓	V	1700	4	2
	1530	✓	✓	2000	4	3
	1730	✓	✓	2400	4	3
	2030	✓	✓	2600	4	4

OTHER COLORS OF PANELS CAN BE ORDERED SEPARATELY.

- panels are terminated on one side with 30 mm barbs, and on the other side they are dull with horizontal wire
- panels can be installed with barbs facing upward or downword, as necessary
- installation with anti-burrowing boards
- quick installation
- highest quality
- we offer a wide variety of double wing, single wing gates and gateways with the same fillings for all heights

USE: private properties, public areas, parks and sports grounds...



Address: Mokrovraty 177 | 262 03 Novy Knin - Czech Republic | Phone: +420 318 593 878 | Fax: +420 318 593 849 |

E-mail: export@pilecky.cz

Accessory for installation of welded panels PILOFOR®

Accessory i	or mistaliation of Weided po	ancis i ilo
description		
44	sleeve PVC for anchoring panels PILOFOR® LIGHT to round posts 48 mm, including bolt	green
		black
		grey
J 3	galvanized clamp for posts Ø 48 mm	terminal
	<u> </u>	continuous
C 2	galvanized + PVC RAL 6005 clamp for posts Ø 48 mm	terminal
		continuous
	clamp for posts \varnothing 48 mm, PVC including screw	green
		black
	clamp for PILOFOR® LIGHT RAL 6005 - green	galvanized
		galvanized + PVC
ADA	clamp for PILOFOR ° stainless steel – butterfly	
	post cap Ø 48 mm including front hooks	green

description		
	clamp for post 60 × 40 mm, galvanized	terminal
200	Salvanizcu	continuous
		corner
FR	clamp for post 60 × 40 mm, galvanized + PVC RAL 6005 - green	terminal
A STATE	gardinzed () ve () (E doos) green	continuous
		corner
TETE	clamp for post 60 × 40 mm, galvanized + PVC RAL 7016 – anthracite	terminal
	I salvanized () Ve (V(E) old antinuente	continuous
-		corner
1010	clamp for posts 60 × 60 mm, green	terminal
	NEW NEW	continuous
1010	clamp for posts 60 × 60 mm, black RAL 9005	terminal
101	NEW NEW	continuous
	clamp PVC for anchoring panels PILOFOR® to posts 60 × 40 mm, including screw	green
	to posts oo x to thin, including selecti	black
4	PILOFOR® panel bracket for post or wall green RAL 6005, black RAL 9005	green
	SICCITIVAE 0003, DIBERTIAL 3003	black
6'	stainless steel braces to wall (2 pcs in package)	
000	(5 hrs III harvage)	



black

Address: Mokrovraty 177 | 262 03 Novy Knin – Czech Republic | Phone: +420 318 593 878 | Fax: +420 318 593 849 | E-mail: export@pilecky.cz