





Industrial welded panels PILOFOR® CLASSIC

- · rectangular loops
- anchoring to posts with square profile (CLASSIC, SUPER, SUPER STRONG)
- panel width 2500 mm
- modified galvanized and galvanized + PVC RAL 6005 green, RAL 7016 anthracite

PILOFOR® CLASSIC PANELS WITH PROFILE

description	height (mm)	CLASSIC self coloured	CLASSIC welded pre-galvanized wires	recommended post height	recommended number of anchorings to post	number of incorporated "V" shapes
eyelets	1030	V	V	1500	3	2
50 × 200 mm	1230	V	✓	1700	4	2
wire diameter 5 mm	1530	✓	✓	2000	4	3
	1730	V	✓	2200	5	3
	2030	~	✓	2600	6	4

INTENDED FOR ADDITIONAL **SURFACE FINISH**

description	height (mm)	CLASSIC galvanized	recommended post height	recommended number of anchorings to post	number of incorporated "V" shapes
eyelets	1030	V	1500	3	2
50 × 200 mm	1230	V	1700	4	2
wire diameter 5 mm	1530	✓	2000 4 3	3	
	1730	✓	2200	5	3
	2030	✓	2600	6	4
	2430	✓	3200	7	4

description	height (mm)	CLASSIC galvanized + PVC RAL 6005	CLASSIC galvanized + PVC RAL 7016	recommended post height	recommended number of anchorings to post	number of incorporated "V" shapes
eyelets	1030	V	V	1500	3	2
50 × 200 mm	1230	✓	✓	1700	4	2
wire diameter 5 mm	1530	✓	✓	2000	4	3
	1730	✓	✓	2200	5	3
	2030	V	✓	2600	6	4
	2430	V	-	3200	7	4

OTHER COLORS OF PANELS CAN BE ORDERED SEPARATELY.

- panels are terminated on one side with 30 mm barbs, and on the other side they are dull with horizontal wire
- · panels can be installed with barbs upward as necessary
- · installation with anti-burrowing boards
- quick installation
- highest quality
- · we offer a wide variety of double wing, single wing gates and gateways with the same fillings for all heights

USE: industrial buildings, factories, schools, parks, fields...

Address: Mokrovraty 177 | 262 03 Novy Knin - Czech Republic | Phone: +420 318 593 878 | Fax: +420 318 593 849 E-mail: export@pilecky.cz www.pilecky.cz

Accessory for installation of welded nanels PII NFNP°

escription	panels PILOFOR [®]	
escription	galvanized clamp for posts Ø 48 mm	terminal
200	3	continuous
٠.	galvanized + PVC RAL 6005	terminal
10 B	clamp for posts Ø 48 mm	continuous
	clamp for posts ∅ 48 mm, PVC	green
	including screw	black
99	hook for anchoring panels (including security nut)	
	galvanized clamp for anchoring panels on cornered post	galvanized
- T	clamp for post 60 × 40 mm,	terminal
-	galvanized	continuous
TF.		corner
Pag	clamp for post 60 × 40 mm,	terminal
1000	galvanized + PVC RAL 6005 - green	continuous
-		corner
1000	clamp for post 60 × 40 mm,	terminal
10000	galvanized + PVC RAL 7016 – anthracite	continuous
-4		corner
16 10	clamp for posts 60 × 60 mm,	terminal
100	green	continuous
10 10	clamp for posts 60 × 60 mm,	terminal
100	black RAL 9005	continuous
150	clamp for rectangular post PILODEL® PRO	green
3	60 × 40 mm stainless steel	black
-	clamp PVC for anchoring panels PILOFOR ®	green
	to posts 60 × 40 mm, including screw	black
100	stainless steel panel fitting for infinite mounting	
	pliers CLASSIC for stainless steel panel fittings	
	stainless steel braces to wall (2 pcs in package)	
	PILOFOR® panel bracket for post or wall	green
1.2	green RAL 6005, black RAL 9005	black
	clamp PVC for anchoring panels to square posts	green
		black
		grey
1 111 1		white
1	clamp PVC for panels to the single or double swing gate frame	
A	clamp stainless steel for panels	
	to the single or double swing gate frame	

security bolt with breaking off head for anchoring

the clamp, galvanized

galvanized M6 bolt

clamp for PILOFOR® stainless steel - butterfly clamp PVC for posts 60 × 40 mm to fix panels **PILOFOR**®

clamp for PILOFOR® - ST

on post 60 × 40 mm, PVC

clamp for PILOFOR® - PRO

clamp for panel **PILOFOR®** with shoulders

for post 60 × 40 mm, metal clip, PVC


on post 60 × 40 mm, PVC

post cap 60 × 40 mm

including front hooks

including front hooks

post cap ∅ 48 mm











Address: Mokrovraty 177 | 262 03 Novy Knin - Czech Republic | Phone: +420 318 593 878 | Fax: +420 318 593 849 | E-mail: export@pilecky.cz

length 42 mm

length 52 mm

length 40 mm

green black

green

black