



Industrial welded panels

PILOFOR® SUPER

- rectangular loops
- anchoring to posts with square profile (**CLASSIC, SUPER, SUPER STRONG**)
- panel width 2500 mm
- modified galvanized and galvanized + PVC RAL 6005 – green, RAL 7016 – anthracite

PILOFOR® SUPER FLAT PANELS

description	height (mm)	SUPER self coloured	SUPER welded pre-galvanized wires	SUPER galvanized	recommended post height	recommended number of anchorings to post
eyelets 50 × 200 mm diameter of wires: horizontal 2 × 6 mm vertical 5 mm	1030	–	✓	✓	1500	3
	1230	–	✓	✓	1700	4
	1430	✓	✓	✓	2000	4
	1630	✓	✓	✓	2200	5
	1830	✓	✓	✓	2400	5
	2030	✓	✓	✓	2600	6
	2430	–	–	✓	3200	7

INTENDED FOR ADDITIONAL SURFACE FINISH

description	height (mm)	SUPER galvanized + PVC RAL 6005	SUPER galvanized + PVC RAL 7016	recommended post height	recommended number of anchorings to post
eyelets 50 × 200 mm diameter of wires: horizontal 2 × 6 mm vertical 5 mm	1030	✓	✓	1500	3
	1230	✓	✓	1700	4
	1430	✓	✓	2000	4
	1630	✓	✓	2200	5
	1830	✓	✓	2400	5
	2030	✓	✓	2600	6
	2430	✓	–	3200	7



























OTHER COLORS OF PANELS CAN BE ORDERED SEPARATELY.

- extremely strong panel thanks to doubled horizontal wires
- panels are terminated on one side with 30 mm barbs, and on the other side they are dull with horizontal wire
- panels can be installed with barbs upward or downward, as necessary
- installation with anti-burrowing boards
- quick installation
- highest quality
- high level of safety
- we offer a wide variety of double wing, single wing gates and gateways with fillings for all heights
- optional accessories include elements with the highest level of protection (trespasser saw, barbwire, razor blade spiral and strip)



USE: airports, military areas, industrial buildings, factories, warehouses and sports stadiums...

Accessory for installation of welded panels **PILOFOR®**

description		
	galvanized clamp for posts Ø 48 mm	terminal continuous
	galvanized + PVC RAL 6005 clamp for posts Ø 48 mm	terminal continuous
	clamp for posts Ø 48 mm, PVC including screw	green black
	galvanized clamp for anchoring panels on cornered post	galvanized
	clamp for post 60 x 40 mm, galvanized	terminal continuous corner
	clamp for post 60 x 40 mm, galvanized + PVC RAL 6005 - green	terminal continuous corner
	clamp for post 60 x 40 mm, galvanized + PVC RAL 7016 - anthracite	terminal continuous corner
	clamp for posts 60 x 60 mm, green	terminal continuous
	clamp for posts 60 x 60 mm, black RAL 9005	terminal continuous
	clamp for rectangular post PILODEL® PRO 60 x 40 mm stainless steel	green black
	clamp PVC for anchoring panels PILOFOR® to posts 60 x 40 mm, including screw	green black
	corner clamp for panel PILOFOR® SUPER	
	stainless steel braces to wall (2 pcs in package)	
	PILOFOR® panel bracket for post or wall green RAL 6005, black RAL 9005	green black
	clamp PVC for anchoring panels to square posts	green black grey white
	clamp PVC for panels to the single or double swing gate frame	
	clamp stainless steel for panels to the single or double swing gate frame	
	security bolt with breaking off head for anchoring the clamp, galvanized	length 42 mm length 52 mm
	galvanized M6 bolt	length 40 mm
	clamp for PILOFOR® stainless steel - butterfly	
	clamp PVC for posts 60 x 40 mm to fix panels PILOFOR®	green black
	clamp for PILOFOR® - ST on post 60 x 40 mm, PVC	green black
	clamp for PILOFOR® - PRO on post 60 x 40 mm, PVC	green black
	clamp for panel PILOFOR® with shoulders for post 60 x 40 mm, metal clip, PVC	green black
	post cap 60 x 40 mm including front hooks	green black
	post cap Ø 48 mm including front hooks	green black

