



Industrial welded panels PILOFOR® SUPER STRONG

- rectangular loops
- anchoring to posts with square profile (**CLASSIC, SUPER, SUPER STRONG**)
- panel width 2500 mm
- modified galvanized and galvanized + PVC RAL 6005 – green, RAL 7016 – anthracite

IN STOCK

PILOFOR® SUPER STRONG FLAT PANELS

| description | height (mm) | SUPER STRONG galvanized | SUPER STRONG galvanized + PVC RAL 6005 | SUPER STRONG galvanized + PVC RAL 7016 | recommended post height | recommended number of anchorings to post |
|---|----------------|----------------------------|--|--|----------------------------|--|
| eyelets 50 × 200 mm diameter of wires: horizontal 2 × 8 mm vertical 6 mm | 1030 | ✓ | ✓ | ✓ | 1500 | 3 |
| | 1230 | ✓ | ✓ | ✓ | 1700 | 4 |
| | 1430 | ✓ | ✓ | ✓ | 2000 | 4 |
| | 1630 | ✓ | ✓ | ✓ | 2200 | 5 |
| | 1830 | ✓ | ✓ | ✓ | 2400 | 5 |
| | 2030 | ✓ | ✓ | ✓ | 2600 | 6 |
| | 2430 | ✓ | ✓ | ✓ | 3200 | 7 |

OTHER COLORS OF PANELS CAN BE ORDERED SEPARATELY.





























- extremely strong panel thanks to doubled horizontal wires
- panels are terminated on one side with 30 mm barbs, and on the other side they are dull with horizontal wire
- panels can be installed with barbs upward or downward, as necessary
- installation with anti-burrowing boards
- quick installation
- highest quality
- high level of safety
- we offer a wide variety of double wing, single wing gates and gateways with fillings for all heights
- optional accessories include elements with the highest level of protection (trespasser saw, barbwire, razor blade spiral and strip)



USE: airports, military areas, industrial buildings, factories, warehouses and sports stadiums...

Accessory for installation of welded panels **PILOFOR®**

| description | | |
|---|---|----------------------------------|
|  | galvanized clamp for posts Ø 48 mm | terminal continuous |
|  | galvanized + PVC RAL 6005 clamp for posts Ø 48 mm | terminal continuous |
|  | clamp for posts Ø 48 mm, PVC including screw | green black |
|  | galvanized clamp for anchoring panels on cornered post | galvanized |
|  | clamp for post 60 x 40 mm, galvanized | terminal continuous corner |
|  | clamp for post 60 x 40 mm, galvanized + PVC RAL 6005 - green | terminal continuous corner |
|  | clamp for post 60 x 40 mm, galvanized + PVC RAL 7016 - anthracite | terminal continuous corner |
|  | clamp for posts 60 x 60 mm, green | terminal continuous |
|  | clamp for posts 60 x 60 mm, black RAL 9005 | terminal continuous |
|  | clamp for rectangular post PILODEL® PRO 60 x 40 mm stainless steel | green black |
|  | clamp PVC for anchoring panels PILOFOR® to posts 60 x 40 mm, including screw | green black |
|  | corner clamp for panel PILOFOR® SUPER | |
|  | stainless steel braces to wall (2 pcs in package) | |
|  | PILOFOR® panel bracket for post or wall green RAL 6005, black RAL 9005 | green black |
|  | clamp PVC for anchoring panels to square posts | green black grey white |
|  | clamp PVC for panels to the single or double swing gate frame | |
|  | clamp stainless steel for panels to the single or double swing gate frame | |
|  | security bolt with breaking off head for anchoring the clamp, galvanized | length 42 mm length 52 mm |
|  | galvanized M6 bolt | length 40 mm |
|  | clamp for PILOFOR® stainless steel - butterfly | |
|  | clamp PVC for posts 60 x 40 mm to fix panels PILOFOR® | green black |
|  | clamp for PILOFOR® - ST on post 60 x 40 mm, PVC | green black |
|  | clamp for PILOFOR® - PRO on post 60 x 40 mm, PVC | green black |
|  | clamp for panel PILOFOR® with shoulders for post 60 x 40 mm, metal clip, PVC | green black |
|  | post cap 60 x 40 mm including front hooks | green black |
|  | post cap Ø 48 mm including front hooks | green black |

